

## Metrische ISO-Gewinde DIN 13-1

Fett und gelb markiert sind gängige Gewinde (Schweiz)

Gewinde Durchmesser M	Steigung mm	Kernloch Mutter mm
1,0	0,25	0,78
1,1	0,25	0,83
1,2	0,25	0,93
1,4	0,30	1,08
1,6	0,35	1,22
1,8	0,35	1,42
2,0	0,40	1,57
2,2	0,45	1,71
2,5	0,45	2,01
<b>3,0</b>	<b>0,50</b>	<b>2,46</b>
3,5	0,60	2,85
<b>4,0</b>	<b>0,70</b>	<b>3,24</b>
4,5	0,75	3,69
<b>5,0</b>	<b>0,80</b>	<b>4,13</b>
<b>6,0</b>	<b>1,00</b>	<b>4,92</b>
7,0	1,00	5,92
<b>8,0</b>	<b>1,25</b>	<b>6,65</b>
9,0	1,25	7,65
<b>10,0</b>	<b>1,50</b>	<b>8,38</b>
11,0	1,50	9,38
<b>12,0</b>	<b>1,75</b>	<b>10,11</b>
14,0	2,00	11,84
<b>16,0</b>	<b>2,00</b>	<b>13,84</b>
18,0	2,50	15,29
<b>20,0</b>	<b>2,50</b>	<b>17,29</b>
22,0	2,50	19,29
<b>24,0</b>	<b>3,00</b>	<b>20,75</b>
27,0	3,00	23,75
<b>30,0</b>	<b>3,50</b>	<b>26,21</b>
33,0	3,50	29,21
<b>36,0</b>	<b>4,00</b>	<b>31,67</b>
39,0	4,00	34,67
42,0	4,50	37,13
45,0	4,50	40,13
48,0	5,00	42,59
52,0	5,00	46,59
56,0	5,50	50,05
60,0	5,50	54,05
64,0	6,00	57,51
68,0	6,00	61,51